



**KNAUF**CEILING  
Solutions

# 阿姆斯壮 特摩风®



- 特摩风矿棉天花板采用白色具有声学效果的吸音透声膜，呈现出光滑，设计现代的表面。同时拥有优秀的吸音功能让其显得与众不同
- 杰出的吸音效果(NRC 0.75 )
- 良好的反光度88%
- 洁净等级高达ISO 4
- 更适用于办公，教育环境



边角类型		明架平板 	直角跌级 														
厚度 (mm)		15															
尺寸 (mm)		600 x 600															
质量		2.9 千克/平方米															
颜色		白色															
隔音		EN ISO 10848-2 D <sub>n,f,w</sub> = 28 dB as per EN ISO 717-1															
吸音性能		$\alpha_w = 0.75$ as per EN ISO 11654:1997 <table border="1"> <thead> <tr> <th>Frequency f (HZ)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>as</td> <td>0.47</td> <td>0.64</td> <td>0.68</td> <td>0.74</td> <td>0.88</td> <td>0.95</td> </tr> </tbody> </table> NRC = 0.75 as per ASTM C423		Frequency f (HZ)	125	250	500	1000	2000	4000	as	0.47	0.64	0.68	0.74	0.88	0.95
Frequency f (HZ)	125	250	500	1000	2000	4000											
as	0.47	0.64	0.68	0.74	0.88	0.95											
防火等级		Euroclass A2-s1,do as per EN 13501-1; <b>Class A</b> (China standard - GB/T 14402); A级 (适用于燃烧热值实验, 中国标准)															
反光度		88%															
热阻值		$\lambda = 0.040$ W/m K as per EN 12667															
防潮等级		防潮等级 <b>95%RH</b>															
洁净室		ISO 4 as per EN ISO 14644-1															
室内空气质量	 A+ 低有机挥发物释放    芬兰低有机挥发物释放    德国低有机挥发物释放																
可清洁性	 可擦洗    干布擦洗																
可持续性	 42%回收材料																