




**KNAUF**CEILING  
Solutions

# ARMSTRONG ANF<sup>®</sup>



- Armstrong ANF is a value-for-money product with a structured and ground surface
- Excellent light reflectance (85%)
- Ideal for retail environments



<b>Edge details</b>		Board 	Tegular 24 	Tegular 15 BE 														
<b>Thickness (mm)</b>		14	14	14														
<b>Dimensions (mm)</b>		600 x 600 600 x 1200	600 x 600 600 x 1200	600 x 600 600 x 1200														
<b>System</b>		PeakForm 888 Prelude XL 32	PeakForm 888 Select	Select PeakForm Suprafine XI														
<b>Weight</b>		<b>3.5 kg/m<sup>2</sup></b> (0.72 lbs/SF)																
<b>Colour</b>		White																
<b>Sound attenuation</b>		CAC = <b>30</b>																
<b>Sound absorption</b>		$\alpha_w = \mathbf{0.50}$ as per EN ISO 11654:1997 <b>Class D</b> <table border="1"> <thead> <tr> <th>Frequency f (HZ)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>as</td> <td>0.33</td> <td>0.31</td> <td>0.38</td> <td>0.57</td> <td>0.61</td> <td>0.55</td> </tr> </tbody> </table> NRC = <b>0.45</b> as per ASTM C423-17			Frequency f (HZ)	125	250	500	1000	2000	4000	as	0.33	0.31	0.38	0.57	0.61	0.55
Frequency f (HZ)	125	250	500	1000	2000	4000												
as	0.33	0.31	0.38	0.57	0.61	0.55												
<b>Fire reaction</b>		US: <b>Class A</b> - Flame Spread 25 or Under; <b>Class 0 / Class 1</b> based on BS 476 Pt - 6 & 7; <b>Class A</b> (China standard - GB/T 14402)																
<b>Light reflectance</b>		<b>85%</b>																
<b>Thermal conductivity</b>		R Factor - <b>1.50</b> (BTU units) R Factor - <b>0.26</b> (Watts units)																
<b>Humidity resistance</b>		<b>RH90</b>																
<b>Sustainability</b>	Recycled Content 41%  China Green Product Label  Member of China GBC  LEED Qualify for LEED Credits																	

