



HERADESIGN® Superfine A2 (fibre width 1mm) 合睿木丝吸音板 (超细纹、非燃性、纤维宽度1毫米)

- HERADESIGN® fine offering very good sound-absorbing properties due to HERADESIGN® wood wool tiles, excellent sound absorption NRC 0.60
由于木丝材料吸声效果优异，提供更优吸音效果，吸声性能高达NRC 0.60
- HERADESIGN® superfine A2 are available in fire resistance class A2 – s1, d0
防火性能高，燃烧等级为A2级的不燃型木丝板
- This superfine texture structure offers more noble and exquisite character and visual enjoyment
超细纹表面结构更高贵精致，视觉效果更佳
- Ideal for Education, Lifestyle, Sports & Leisure environments
适用于教育、生活休闲、体育娱乐等领域



HERADESIGN® Superfine A2 (fibre width 1mm)



合睿木丝吸音板 (超细纹、非燃性、纤维宽度1毫米)

Panel Options 天花板选择	AK-01 暗架系统	SK-04 明架系统	
Edge Design 边角设计	 四边倒角 (倒边5毫米)	 所有边均为直角边	
Dimensions(mm) 尺寸	600X 1200X 15mm 600X 1200X 25mm	600X 600X 25mm	
Thickness(mm) 厚度			
Grid Dimensions(L/W(mm)) 龙骨尺寸	上层龙骨间距: 900mm 下层龙骨间距: 600mm (25mm) 耐球冲击: 上层龙骨间距: 900mm 下层龙骨间距: 300mm (25mm) 上层龙骨间距: 900mm 下层龙骨间距: 400mm (15mm)	600x600mm	
Recommended Section Width 建议龙骨宽度	60mm	24mm	
Weight 质量	19.0kg/m ² (25mm) 19.0公斤/平方米(25mm)	11.8kg/m ² (15mm) 11.8公斤/平方米(15mm)	Colour 颜色 Nature 自然色
Sound absorption 吸音性能	$\alpha_w=0.60$ (LH) (25mm) Frequency f (HZ) 125 250 500 1000 2000 4000 α_s 0.29 0.66 0.59 0.48 0.60 0.84 NRC=0.60	$\alpha_w=0.60$ (LH) (15mm) Frequency f (HZ) 125 250 500 1000 2000 4000 α_s 0.31 0.73 0.74 0.48 0.54 0.49 NRC=0.60	
Fire reaction 防火等级	防火性能达到DIN-EN 13501-1标准: A2-s1, d0 中国标准GB8624: A级 (适用于燃烧热值实验-GB/T 14402, 中国标准)	Humidity resistance 防潮等级 RH90 防潮等级RH90	

浏览测试报告

Ball impact resistant ceiling panelling according to DIN 18 032 / Teil 3
天花耐球冲击按照DIN 18 032/ Teil 3

Construction 结构	Product 产品	Substructure 龙骨系统	Center distance Support profile 龙骨间距	Installation 安装	Fastening 固定方式	
	HERADESIGN® superfine A2 Thickness: 25 mm Format: 1200 x 600 超细纹A2木丝板 厚度: 25mm 尺寸: 1200X600	CD sections 60x27x0,6 mm CD龙骨 60x27x0.6mm	Single layer 单层龙骨 Double layer 双层龙骨	下层龙骨 ≤ 300 mm 上层龙骨 ≤ 900 mm	Transverse to substructure 短边平行龙骨	HERADESIGN® screw 9 pcs/panel 9个螺钉每块板

Ball impact resistant wall panelling according to DIN 18 032 / Teil 3
墙面耐球冲击按照DIN 18 032/ Teil 3

Construction 结构	Product 产品	Substructure 龙骨系统	Center distance Support profile 龙骨间距	Installation 安装	Fastening 固定方式	
	HERADESIGN® superfine A2 Thickness: 25 mm Format: 1200 x 600 超细纹A2木丝板 厚度: 25mm 尺寸: 1200X600	CD sections 60x27x0,6 mm CD龙骨 60x27x0.6mm	Single layer 单层龙骨 Double layer 双层龙骨	下层龙骨 ≤ 300 mm 上层龙骨 ≤ 900 mm	Transverse to substructure 短边平行龙骨	HERADESIGN® screw 9 pcs/panel 9个螺钉每块板



扫描二维码
获取详细的产品信息

关注阿姆斯壮天花公众号
获取更多精彩内容

www.knaufarmstrong.com

免费咨询热线: 400-779-3366

12-2020 Printed in Shanghai

Heradesign®
Acoustic Ceilings